TURBO JET

DAILY ROUTINE MAINTENANCE

Daily maintenance must be carried out by specially instructed surgery staff





- Always refer to the operator's handbook before carrying out any work
- Manuals are available on the website www.cattaniesam.it
- We recommend their consultation especially for updates about safety
- Prior to carrying out any servicing operation make sure to wear disposable gloves, goggles, a mask and overalls
- Disconnect the appliance from the power
- Keep the plant room free from flammable and corrosive mixtures














CHECK

- 1) Check for any possible audible / visible alarms.
- 2) At the end of every working day aspirate a solution of Puli-Jet Plus using Pulse Cleaner.

General Cleaning (daily): mix 10ml of Puli-Jet Plus with 2.5 litres of warm water (approx temp 50° c).

Disinfecting (once per week): mix 20ml of Puli-Jet with 2.5 litres of warm water (approx temp 50° c).

 Clean the aspiration filters on the dental unit and replace Antifoaming Tablets (if used).







4) Clean and disinfect the aspirator filter







Annual maintenance must be carried out by a trained engineer in possession of original spare parts

HOW IS IT WE LEAD IN OUR FIELD, WHEN WE COST LESS THAN THE ALTERNATIVES? THIS IS HOW:

Constant research: this lets us apply the latest technology in all of our products and solutions.

We enhance performance: electronic and information technology allow us to increase the performance and reliability of our products.

We reduce costs: less maintenance and energy costs mean on a cost-benefit analysis we are always the most economical.

 $\textbf{We reduce environmental impact:} \ we \ save \ 50\% \ of \ primary \ materials, \ and \ allow \ you \ to \ save \ between \ 30\% \ and \ 50\% \ of \ electrical \ consumption.$



TURBO JET

ANNUAL ROUTINE MAINTENANCE

Annual maintenance must be carried out by a trained engineer in possession of original spare parts





- Always refer to the operator's handbook before carrying out any work
- Manuals are available on the website www.cattaniesam.it
- We recommend their consultation especially for updates about safety
- Prior to carrying out any servicing operation make sure to wear disposable gloves, goggles, a mask and overalls
- Disconnect the appliance from the power
- Keep the plant room free from flammable and corrosive mixtures













CHECK

1) Check for any possible audible / visible alarms





2) Routine maintenance has been duly carried out and make sure that Magnolia products are used*.







CHECK SERVICING REQUIREMENTS

The following servicing requirements should ONLY be carried out by a trained engineer.

The following items below need to be replaced, making sure that when reassembled all O-rings on amalgam container and debris filter are lubricated with Lubri-Jet spray or drop. Use only silicone based lubricants.

SERV-TJA basic kit

041402	11.7mm tube
189106	10mfd capacitor for A/W Sep
200955	A/Sep orifice plate
201179	10mm elbow
210815	Recirculation valve diaphragm
210904	A/Sep orifice plate small 0-ring
210909	Mini-Sep entry 0-ring
210910	O-ring for flow valve system (large)
210912	O-ring inline debris filter inlet
210933	O-ring for flow valve system (small)
210943	Amalgam Sep pot 0-ring IS0
210949	A/Sep orifice plate large O-ring
210966	O-ring for A/W Sep motor
210975	O-ring for Air Inlet Seal
211600	Rubber non return valve
224961	Water outlet valve ISO4
250547	Spring for ISO4 waste outlet valve
250548	Recirculation valve spring

SERV-TJB complete kit

041402	11.7mm tube
043133	Amalgam pot
189106	10mfd capacitor for A/W Sep and suction motor
200955	A/Sep orifice plate
201179	10mm elbow
202573	New recirculation valve complete
210904	A/Sep orifice plate small 0-ring
210909	Mini-Sep entry 0-ring
210910	O-ring for flow valve system (large)
210912	O-ring inline debris filter inlet
210933	0-ring for flow valve system (small)
210943	Amalgam Sep pot 0-ring ISO
210949	A/Sep orifice plate large O-ring
210966	0-ring for A/W Sep motor
210975	O-ring for Air Inlet Seal
211600	Rubber non return valve
224961	Water outlet valve ISO4
240317	0040 inline debris filter
250547	Spring for ISO4 waste outlet valve







* Where routine maintenance is not carried out properly or unsuitable products are used, inform the staff and practice manager.

HOW IS IT WE LEAD IN OUR FIELD, WHEN WE COST LESS THAN THE ALTERNATIVES? THIS IS HOW:

Constant research: this lets us apply the latest technology in all of our products and solutions.

We enhance performance: electronic and information technology allow us to increase the performance and reliability of our products.

We reduce costs: less maintenance and energy costs mean on a cost-benefit analysis we are always the most economical.

We reduce environmental impact: we save 50% of primary materials, and allow you to save between 30% and 50% of electrical consumption.

